Garant

Solid carbide milling cutter MTC, DLC, Ø DC: 12 mm



Order data

Order number	202270 12
GTIN	4045197654977
Item class	11X

Description

Version:

With the latest generation of **DLC coating sp**².

Eccentric relief ground, additionally **polish ground** in the flutes for **outstanding chip evacuation** in long-chipping aluminium components.

Lengths similar to DIN 6527 long.

Application:

Especially for **MTC (Multi Task Cutting)** use on the new generation of turning / milling centres. **Note:**

NEW GENERATION AVAILABLE!

Recommended successor products are No. 202004 and No. 202010.

Tolerance nominal \emptyset : h6 No. of teeth Z: 3 Helix angle: 45 degrees Direction of infeed: horizontal, oblique and vertical Shank: DIN 6535 HA to h6 Balance quality with shank: G 2.5 with HA No. of teeth Z: 3 Flute length L_c: 26 mm Overhang length L₁ incl. recess: 36 mm Recess \emptyset D₁: 11 mm Overall length L: 83 mm Shank \emptyset D₃: 12 mm

Technical description

Recess $\emptyset D_1$

11 mm

Corner chamfer width at 45°	0.2 mm
Cutting edge Ø D _c	12 mm
Overhang length L ₁ incl. recess	36 mm
Feed f_z for side milling in short-chipping aluminium	0.07 mm
No. of teeth Z	3
Shank form	HA
Feed f_z for slot milling in short-chipping aluminium	0.05 mm
Shank Ø D _s	12 mm
Overall length L	83 mm
Flute length L _c	26 mm
Direction of infeed	horizontal, oblique and vertical
Shank	DIN 6535 HA to h6
Tolerance nominal Ø	h6
Balance quality with shank	G 2.5 with HA
Helix angle	45 degrees
Corner chamfer angle	45 degrees
Coating	DLC
Tool material	Solid carbide
Standard	DIN 6527
Туре	W
Helix angle characteristic	unequal spacing
Cutting width a_e for milling operation	0.5×D for side milling
Cutting width a_e for milling operation	Full slot cutting depth 1×D
Through-coolant	no
Machining strategy	MTC
Colour ring	yellow
Type of product	End mill
••••••	

Services

Shank recess Type FRST	209900 FRST
Shank clamping flats for shrink-fit chucks, with retainer function Shank Ø tool 12 mm	SZ2025 12
Shank grinding Type HB	129100 HB