

Solid carbide milling cutter MTC, DLC, Ø DC: 20M mm



Order data

Order number	202270 20M
GTIN	4045197763976
Item class	11X

Description

Version:

With the latest generation of **DLC coating sp** 2 .

Eccentric relief ground, additionally **polish ground** in the flutes for **outstanding chip evacuation** in long-chipping aluminium components.

Lengths similar to **DIN 6527 long.**

Application:

Especially for MTC (Multi Task Cutting) use on the new generation of turning / milling centres.

Note:

NEW GENERATION AVAILABLE!

Recommended successor products are No. 202004 and No. 202010.

Tolerance nominal Ø: h6

No. of teeth Z: 3

Helix angle: 45 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HB to h6

Balance quality with shank: G 2.5 with HB

No. of teeth Z: 3

Flute length L_c: 60 mm

Overhang length L₁ incl. recess: 74 mm

Recess \emptyset D₁: 19 mm Overall length L: 126 mm Shank \emptyset D_s: 20 mm

Technical description

Feed f _z for slot milling in short-chipping aluminium	0.085 mm
--	----------

Direction of infeed	horizontal, oblique and vertical
Corner chamfer width at 45°	0.2 mm
No. of teeth Z	3
Recess Ø D ₁	19 mm
Flute length L _c	60 mm
Overhang length L ₁ incl. recess	74 mm
Feed f _z for side milling in short-chipping aluminium	0.12 mm
Overall length L	126 mm
Balance quality with shank	G 2.5 with HB
Shank form	НВ
Cutting edge Ø D _C	20 mm
Shank	DIN 6535 HB to h6
Tolerance nominal Ø	h6
Shank Ø D _s	20 mm
Helix angle	45 degrees
Corner chamfer angle	45 degrees
Coating	DLC
Tool material	Solid carbide
Standard	DIN 6527
Туре	W
Helix angle characteristic	unequal spacing
Cutting width a _e for milling operation	0.5×D for side milling
Cutting width a _e for milling operation	Full slot cutting depth 1×D
Through-coolant	no
Machining strategy	MTC
Colour ring	yellow
Type of product	End mill

Services

Shank clamping flats for shrink-fit chucks, with retainer function Shank Ø tool 20 mm

SZ2025 20