Garant

Solid carbide milling cutter MTC, DLC, Ø DC: 20 mm



Order data

Order number	202272 20
GTIN	4045197655066
Item class	11X

Description

Version:

With the latest generation of **DLC coating sp**².

Eccentric relief ground, additionally **polish ground** in the flutes for **outstanding chip evacuation** in long-chipping aluminium components.

Without 45° corner chamfer.

Lengths similar to **DIN 6527 long.**

Size 1-2 – tolerance: Size nominal \emptyset **D**_c = **e8**.

Size 2.5–20M – tolerance: Size nominal \emptyset **D**_c = **h6**.

Application:

Especially for **MTC (Multi Task Cutting)** use on the new generation of turning / milling centres. Tolerance nominal \emptyset : h6 No. of teeth Z: 3 Helix angle: 45 degrees Direction of infeed: horizontal, oblique and vertical Shank: DIN 6535 HB to h6 Balance quality with shank: G 2.5 with HB No. of teeth Z: 3 Flute length L_c: 41 mm Overhang length L₁ incl. recess: 52 mm Recess \emptyset D₁: 19 mm Overall length L: 104 mm Shank \emptyset D_c: 20 mm

Technical description

Overhang length L₁ incl. recess

52 mm

No. of teeth Z	3
Shank form	НВ
Recess Ø D ₁	19 mm
Feed f_z for slot milling in short-chipping aluminium	0.085 mm
Cutting edge Ø D _c	20 mm
Feed f_z for side milling in short-chipping aluminium	0.12 mm
Shank Ø D _s	20 mm
Overall length L	104 mm
Flute length L _c	41 mm
Direction of infeed	horizontal, oblique and vertical
Shank	DIN 6535 HB to h6
Tolerance nominal Ø	h6
Balance quality with shank	G 2.5 with HB
Helix angle	45 degrees
Corner chamfer angle	90 degrees
Coating	DLC
Tool material	Solid carbide
Standard	DIN 6527
Туре	W
Helix angle characteristic	unequal spacing
Cutting width a_e for milling operation	0.5×D for side milling
Cutting width a_e for milling operation	Full slot cutting depth 1×D
Through-coolant	no
Machining strategy	MTC
Colour ring	yellow
Type of product	End mill

Services

Shank recess Type FRST

209900 FRST

© Hoffmann GmbH Qualitätswerkzeuge

Shank clamping flats for shrink-fit chucks, with retainer function Shank \varnothing tool 20 mm

SZ2025 20