

Solid carbide milling cutter MTC, DLC, Ø DC: 20M mm



Order data

Order number	202272 20M
GTIN	4045197764638
Item class	11X

Description

Version:

With the latest generation of **DLC coating sp** 2 .

Eccentric relief ground, additionally **polish ground** in the flutes for **outstanding chip evacuation** in long-chipping aluminium components.

Without 45° corner chamfer.

Lengths similar to **DIN 6527 long.**

Size 1–2 – tolerance: Size nominal \varnothing **D**_C = **e8.**

Size 2.5–20M – tolerance: Size nominal \varnothing **D**_C = **h6.**

Application:

Especially for MTC (Multi Task Cutting) use on the new generation of turning / milling centres.

Tolerance nominal Ø: h6

No. of teeth Z: 3

Helix angle: 45 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HB to h6

Balance quality with shank: G 2.5 with HB

No. of teeth Z: 3

Flute length L_c: 60 mm

Overhang length L₁ incl. recess: 74 mm

Recess \emptyset D₁: 19 mm Overall length L: 126 mm Shank \emptyset D₅: 20 mm

Technical description

No. of teeth Z

Balance quality with shank	G 2.5 with HB
Direction of infeed	horizontal, oblique and vertical
Cutting edge Ø D _c	20 mm
Overhang length L ₁ incl. recess	74 mm
Tolerance nominal Ø	h6
Flute length L_c	60 mm
Feed f_z for slot milling in short-chipping aluminium	0.085 mm
Feed f_z for side milling in short-chipping aluminium	0.12 mm
Recess Ø D ₁	19 mm
Overall length L	126 mm
Shank Ø D _s	20 mm
Shank form	НВ
Shank	DIN 6535 HB to h6
Helix angle	45 degrees
Corner chamfer angle	90 degrees
Coating	DLC
Tool material	Solid carbide
Standard	DIN 6527
Type	W
Helix angle characteristic	unequal spacing
Cutting width a _e for milling operation	0.5×D for side milling
Cutting width a _e for milling operation	Full slot cutting depth 1×D
Through-coolant	no
Machining strategy	MTC
Colour ring	yellow
Type of product	End mill

Services

SZ2025 20



Shank clamping flats for shrink-fit chucks, with retainer function Shank Ø tool 20 mm