

## Garant

### Solid carbide milling cutter MTC, DLC, Ø h6 DC: 10 mm



#### Order data

Order number	202273 10
GTIN	4045197860170
Item class	11X

#### Description

##### Version:

With the latest generation of **DLC coating sp<sup>2</sup>**.

**Eccentric relief ground**, additionally **polish ground** in the flutes for **outstanding chip evacuation** in long-chipping aluminium components.

**Without** 45° cutting edge chamfer.

##### Application:

Especially for **MTC (Multi Task Cutting)** use on the new generation of turning / milling centres.

Tolerance nominal Ø: h6

No. of teeth Z: 3

Helix angle: 45 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HA to h6

Balance quality with shank: G 2.5 with HA

No. of teeth Z: 3

Flute length L<sub>c</sub>: 22 mm

Overhang length L<sub>1</sub> incl. recess: 38 mm

Recess Ø D<sub>1</sub>: 9.2 mm

Overall length L: 80 mm

Shank Ø D<sub>s</sub>: 10 mm

#### Technical description

Cutting edge Ø D <sub>c</sub>	10 mm
No. of teeth Z	3
Shank form	HA
Direction of infeed	horizontal, oblique and vertical

Tolerance nominal $\varnothing$	h6
Feed $f_z$ for side milling in short-chipping aluminium	0.05 mm
Overall length L	80 mm
Flute length $L_c$	22 mm
Overhang length $L_1$ incl. recess	38 mm
Feed $f_z$ for slot milling in short-chipping aluminium	0.04 mm
Shank	DIN 6535 HA to h6
Balance quality with shank	G 2.5 with HA
Shank $\varnothing D_s$	10 mm
Recess $\varnothing D_1$	9.2 mm
Helix angle	45 degrees
Corner chamfer angle	90 degrees
Coating	DLC
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	W
Helix angle characteristic	unequal spacing
Cutting width $a_e$ for milling operation	Full slot cutting depth $1 \times D$
Cutting width $a_e$ for milling operation	$0.5 \times D$ for side milling
Through-coolant	no
Machining strategy	MTC
Colour ring	yellow
Type of product	End mill

## Services

Shank grinding Type HB	129100 HB
------------------------	-----------