


Solid carbide end mill, uncoated, Ø e8 DC: 4 mm

Order data

Order number	202276 4
GTIN	4045197865564
Item class	12X

Description
Version:

Dimensions similar to **DIN 6527**.

Through-coolant: no

Tolerance nominal Ø: e8

No. of teeth Z: 3

Helix angle: 30 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HB to h6

No. of teeth Z: 3

Flute length L_c : 8 mm

Overall length L: 54 mm

Shank Ø D_s : 6 mm

Shank form: HB

Corner chamfer width at 45°: 0.18 mm

Technical description

Direction of infeed	horizontal, oblique and vertical
Corner chamfer width at 45°	0.18 mm
Cutting edge Ø D_c	4 mm
Flute length L_c	8 mm
No. of teeth Z	3
Overall length L	54 mm
Shank form	HB

Shank	DIN 6535 HB to h6
Feed f_z for slot milling in steel < 750 N/mm ²	0.02 mm
Tolerance nominal \varnothing	e8
Feed f_z for side milling in steel < 750 N/mm ²	0.025 mm
Shank $\varnothing D_s$	6 mm
Helix angle	30 degrees
Corner chamfer angle	45 degrees
Coating	uncoated
Tool material	Solid carbide
Standard	DIN 6527
Type	N
Cutting width a_e for milling operation	0.3×D for side milling
Cutting width a_e for milling operation	Full slot cutting depth 1×D
Through-coolant	no
Colour ring	without
Type of product	End mill