

Solid carbide milling cutter with internal coolant supply MTC, DLC, Ø DC: 10 mm



Order data

Order number	202278 10
GTIN	4045197655165
Item class	11X

Description

Version:

With the latest generation of **DLC coating sp** 2 .

Eccentric relief ground, additionally **polish ground** in the flutes for **outstanding chip evacuation** in long-chipping aluminium components.

Lengths similar to DIN 6527 long.

Application:

Especially for MTC (Multi Task Cutting) use on the new generation of turning / milling centres.

Note:

NEW GENERATION AVAILABLE!

Recommended successor product is No. 202006.

Tolerance nominal Ø: h6

No. of teeth Z: 3

Helix angle: 45 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HA to h6

Balance quality with shank: G 2.5 with HA

No. of teeth Z: 3

Flute length L_c: 22 mm

Overhang length L₁ incl. recess: 30 mm

Recess \varnothing D₁: 9.2 mm Overall length L: 72 mm Shank \varnothing D₂: 10 mm

Technical description

No. of teeth Z 3

Corner chamfer width at 45°	0.2 mm
Feed f _z for slot milling in short-chipping aluminium	0.04 mm
Feed f _z for side milling in short-chipping aluminium	0.05 mm
Cutting edge Ø D _c	10 mm
Overhang length L ₁ incl. recess	30 mm
Shank form	НА
Recess Ø D ₁	9.2 mm
Shank Ø D _s	10 mm
Overall length L	72 mm
Flute length L _c	22 mm
Direction of infeed	horizontal, oblique and vertical
Shank	DIN 6535 HA to h6
Tolerance nominal Ø	h6
Balance quality with shank	G 2.5 with HA
Helix angle	45 degrees
Corner chamfer angle	45 degrees
Coating	DLC
Tool material	Solid carbide
Standard	DIN 6527
Туре	W
Helix angle characteristic	unequal spacing
Cutting width a _e for milling operation	0.5×D for side milling
Cutting width a _e for milling operation	Full slot cutting depth 1×D
Through-coolant	yes
Machining strategy	MTC
Colour ring	yellow
Type of product	End mill

Services

Shank recess Type FRST	209900 FRST
Shank grinding Type HB	129100 HB