

**Garant**
**Solid carbide slot drill DIN 6535 HA, TiAlN, Ø DC: 7,5 mm**

**Order data**

Order number	202280 7,5
GTIN	4045197116390
Item class	11X

**Description**
**Version:**
**Eccentric relief ground.**

Dimensions similar to **DIN 6527 long series.**

Tolerance: Size nominal Ø  $D_c = e8$ .

Cutting width  $a_e$  for milling operation: Full slot cutting depth  $1 \times D$

Tolerance nominal Ø: e8

No. of teeth Z: 3

Helix angle: 45 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HA to h6

No. of teeth Z: 3

Flute length  $L_c$ : 19 mm

Overhang length  $L_1$  incl. recess: 27 mm

Recess Ø  $D_1$ : 7.3 mm

Overall length L: 63 mm

Shank Ø  $D_s$ : 8 mm

**Technical description**

Cutting edge Ø $D_c$	7.5 mm
Overhang length $L_1$ incl. recess	27 mm
Corner chamfer width at 45°	0.1 mm
No. of teeth Z	3
Feed $f_z$ for slot milling in steel < 900 N/mm <sup>2</sup>	0.03 mm

Recess $\varnothing D_1$	7.3 mm
Feed $f_z$ for side milling in steel $< 900 \text{ N/mm}^2$	0.033 mm
Shank $\varnothing D_s$	8 mm
Overall length L	63 mm
Flute length $L_c$	19 mm
Direction of infeed	horizontal, oblique and vertical
Correction factor for $v_c$	1.5
Shank	DIN 6535 HA to h6
Tolerance nominal $\varnothing$	e8
Helix angle	45 degrees
Corner chamfer angle	45 degrees
Coating	TiAlN
Tool material	Solid carbide
Standard	DIN 6527
Type	N
Cutting width $a_e$ for milling operation	0.5×D for side milling
Cutting width $a_e$ for milling operation	Full slot cutting depth 1×D
Colour ring	without
Type of product	End mill

## Services

Shank grinding Type HB	129100 HB
------------------------	-----------