

Garant

Solid carbide milling cutter TPC, DLC, Ø h6 DC: 6 mm



Order data

Order number	202282 6
GTIN	4045197773227
Item class	11X

Description

Version:

Eccentric relief ground, additionally **polish ground** in the flutes for **outstanding chip evacuation** in long-chipping aluminium workpieces.

With double chip-breaker for exemplary chip formation.

With the latest generation of **DLC coating sp²**.

Note:

$a_{e \max} = 0.12 \times D$ for TPC machining.

h_{\max} : The values stated in the table are maximum values.

NEW GENERATION AVAILABLE! Recommended successor product is No. 203114.

Tolerance nominal Ø: h6

No. of teeth Z: 3

Helix angle: 45 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HA to h6

Balance quality with shank: G 2.5 with HA

No. of teeth Z: 3

Flute length L_c : 25 mm

Overhang length L_1 incl. recess: 30 mm

Recess Ø D_1 : 5.7 mm

Overall length L: 71 mm

Shank Ø D_s : 6 mm

Technical description

Corner chamfer width at 45°	0.2 mm
Balance quality with shank	G 2.5 with HA

Shank form	HA
Direction of infeed	horizontal, oblique and vertical
Tolerance nominal \varnothing	h6
Overall length L	71 mm
Shank	DIN 6535 HA to h6
Shank $\varnothing D_s$	6 mm
No. of teeth Z	3
Flute length L_c	25 mm
Cutting edge $\varnothing D_c$	6 mm
Recess $\varnothing D_1$	5.7 mm
Overhang length L_1 incl. recess	30 mm
Average chip thickness h_{max} for TPC milling in short-chipping aluminium	0.032 mm
Helix angle	45 degrees
Corner chamfer angle	45 degrees
Coating	DLC
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	W
Helix angle characteristic	unequal spacing
Cutting width a_e for milling operation	$0.12 \times D$
Through-coolant	no
Machining strategy	TPC
Colour ring	yellow
Type of product	End mill

Services

Shank grinding Type HB	129100 HB
------------------------	-----------

