

Garant
Solid carbide milling cutter, AlCrN, Ø e8 DC: 2,5 mm

Order data

Order number	202305 2,5
GTIN	4045197931405
Item class	11X

Description
Version:

Dimensions similar to **DIN 6527**.

Improved coating for general-purpose applications in steel and cast iron.

Note:

Successor product to No. 202210.

Through-coolant: no

Tolerance nominal Ø: e8

No. of teeth Z: 3

Helix angle: 45 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HB to h6

No. of teeth Z: 3

Flute length L_c : 4 mm

Overhang length L_1 incl. recess: 10 mm

Recess Ø D_1 : 2.3 mm

Overall length L: 50 mm

Shank Ø D_s : 6 mm

Technical description

Shank	DIN 6535 HB to h6
Overhang length L_1 incl. recess	10 mm
Shank Ø D_s	6 mm
Flute length L_c	4 mm
Overall length L	50 mm

Cutting edge $\varnothing D_c$	2.5 mm
Tolerance nominal \varnothing	e8
Corner chamfer width at 45°	0.1 mm
Feed f_z for side milling in steel < 750 N/mm ²	0.011 mm
Helix angle	45 degrees
Feed f_z for slot milling in steel < 750 N/mm ²	0.01 mm
No. of teeth Z	3
Direction of infeed	horizontal, oblique and vertical
Recess $\varnothing D_1$	2.3 mm
Shank form	HB
Corner chamfer angle	45 degrees
Coating	AlCrN
Tool material	Solid carbide
Standard	DIN 6527
Type	N
Cutting width a_e for milling operation	0.5×D for side milling
Cutting width a_e for milling operation	Full slot cutting depth 1×D
Through-coolant	no
Colour ring	without
Type of product	End mill