

Garant

GARANT Master INOX solid carbide milling cutter HPC, TiAlN, Ø h10 DC: 5,5 mm



Order data

Order number	202387 5,5
GTIN	4045197875181
Item class	11X

Description

Version:

Dimensions similar to **DIN 6527**.

For roughing and finishing

HPC milling cutters with **newly developed high-performance coating** for **outstanding service life** and **optimum metal removal rates** in a wide range of stainless steels.

Greater oxidation resistance and **high-temperature hardness**.

Can be used at **high cutting speeds**, particularly suitable even for TOOLOX®.

Tolerance nominal Ø: h10

No. of teeth Z: 3

Helix angle: 40 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HB to h6

No. of teeth Z: 3

Flute length L_c : 13 mm

Overhang length L_1 incl. recess: 19 mm

Recess Ø D_1 : 5.4 mm

Overall length L: 57 mm

Shank Ø D_s : 6 mm

Technical description

Corner chamfer width at 45°	0.1 mm
Shank Ø D_s	6 mm
Recess Ø D_1	5.4 mm

Cutting edge $\varnothing D_c$	5.5 mm
Feed f_z for side milling in INOX > 900 N/mm ²	0.048 mm
Shank	DIN 6535 HB to h6
Tolerance nominal \varnothing	h10
Overhang length L_1 incl. recess	19 mm
Overall length L	57 mm
No. of teeth Z	3
Feed f_z for slot milling in stainless steel > 900 N/mm ²	0.04 mm
Flute length L_c	13 mm
Direction of infeed	horizontal, oblique and vertical
Helix angle	40 degrees
Corner chamfer angle	45 degrees
Series	GARANT Master INOX
Coating	TiAlN
Tool material	Solid carbide
Standard	DIN 6527
Type	N
Helix angle characteristic	unequal spacing
Spacing of the cutters	unequal spacing
Cutting width a_e for milling operation	Full slot cutting depth $1 \times D$
Cutting width a_e for milling operation	$0.5 \times D$ for side milling
Through-coolant	no
Machining strategy	HPC
Colour ring	blue
Type of product	End mill