

Garant
**GARANT Master Steel PickPocket solid carbide roughing end mill HPC, TiAlN,
 Ø f8 DC: 6,7 mm**

Order data

Order number	202404 6,7
GTIN	4045197779267
Item class	11X

Description
Version:

For **roughing and finishing**

With corner radii similar to torus cutters.

Up to 1×D into solid material **at very high feed rates** with smooth cutting action.

Advantage:

Optimised flute form, eccentric relief ground, wide chip space.

Tolerance nominal Ø: f8

No. of teeth Z: 3

Helix angle: 38 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HB to h6

No. of teeth Z: 3

Flute length L_c : 16 mm

Overhang length L_1 incl. recess: 25 mm

Recess Ø D_1 : 6.5 mm

Overall length L: 63 mm

Shank Ø D_s : 8 mm

Technical description

Cutting edge Ø D_c	6.7 mm
Recess Ø D_1	6.5 mm
Flute length L_c	16 mm
Feed f_z for side milling in steel < 900 N/mm ²	0.05 mm

Shank $\varnothing D_s$	8 mm
No. of teeth Z	3
Feed f_z for slot milling in steel < 900 N/mm ²	0.04 mm
Shank	DIN 6535 HB to h6
Overall length L	63 mm
Tolerance nominal \varnothing	f8
Direction of infeed	horizontal, oblique and vertical
Overhang length L_1 incl. recess	25 mm
Helix angle	38 degrees
Corner rounding r_v	0.34 mm
Series	GARANT Master Steel
Coating	TiAlN
Tool material	Solid carbide
Standard	DIN 6527
Type	N
Helix angle characteristic	unequal spacing
Spacing of the cutters	unequal spacing
Cutting width a_e for milling operation	0.4×D for side milling
Cutting width a_e for milling operation	Full slot cutting depth 1×D
Through-coolant	no
Machining strategy	HPC
Colour ring	green
Type of product	End mill