




## HOLEX Pro Steel solid carbide roughing end mill HPC, TiAlN, Ø DC: 12 mm



### Order data

Order number	202414 12
GTIN	4045197776204
Item class	12X

### Description

#### Version:

For **roughing and finishing**.

Up to 1×D into solid material **at very high feed rates** with smooth cutting action.

#### Advantage:

Optimised flute form, eccentric relief ground, wide chip space.

Tolerance nominal Ø: 0 / -0.03

No. of teeth Z: 3

Helix angle: 45 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HB to h6

No. of teeth Z: 3

Flute length  $L_c$ : 26 mm

Overhang length  $L_1$  incl. recess: 38 mm

Recess Ø  $D_1$ : 11.5 mm

Overall length L: 83 mm

Shank Ø  $D_s$ : 12 mm

### Technical description

Feed $f_z$ for side milling in steel < 900 N/mm <sup>2</sup>	0.09 mm
Cutting edge Ø $D_c$	12 mm
Feed $f_z$ for slot milling in steel < 900 N/mm <sup>2</sup>	0.07 mm
Shank	DIN 6535 HB to h6
Corner chamfer width at 45°	0.3 mm

Flute length $L_c$	26 mm
No. of teeth $Z$	3
Overhang length $L_1$ incl. recess	38 mm
Shank $\varnothing D_s$	12 mm
Direction of infeed	horizontal, oblique and vertical
Tolerance nominal $\varnothing$	0 / -0.03
Overall length $L$	83 mm
Recess $\varnothing D_1$	11.5 mm
Helix angle	45 degrees
Corner chamfer angle	45 degrees
Series	HOLEX Pro Steel
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Helix angle characteristic	unequal spacing
Spacing of the cutters	unequal spacing
Cutting width $a_e$ for milling operation	0.4×D for side milling
Cutting width $a_e$ for milling operation	Full slot cutting depth 1×D
Through-coolant	no
Machining strategy	HPC
Colour ring	green
Type of product	End mill

## Services

Shank clamping flats for shrink-fit chucks, with retainer function Shank  $\varnothing$  tool 12 mm

SZ2025 12