



HOLEX Pro Steel solid carbide roughing end mill HPC, TiAlN, Ø DC: 17,5 mm

Order data

Order number	202414 17,5
GTIN	4045197776259
Item class	12X

Description
Version:

For **roughing and finishing**.

Up to 1×D into solid material **at very high feed rates** with smooth cutting action.

Advantage:

Optimised flute form, eccentric relief ground, wide chip space.

Tolerance nominal Ø: 0 / -0.03

No. of teeth Z: 3

Helix angle: 45 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HB to h6

No. of teeth Z: 3

Flute length L_c : 32 mm

Overhang length L_1 incl. recess: 50 mm

Recess Ø D_1 : 17 mm

Overall length L: 92 mm

Shank Ø D_s : 18 mm

Technical description

Flute length L_c	32 mm
Overhang length L_1 incl. recess	50 mm
Recess Ø D_1	17 mm
Feed f_z for slot milling in steel < 900 N/mm ²	0.1 mm
Cutting edge Ø D_c	17.5 mm

Feed f_z for side milling in steel < 900 N/mm ²	0.13 mm
Corner chamfer width at 45°	0.4 mm
Shank	DIN 6535 HB to h6
Shank $\varnothing D_s$	18 mm
Direction of infeed	horizontal, oblique and vertical
No. of teeth Z	3
Overall length L	92 mm
Tolerance nominal \varnothing	0 / -0.03
Helix angle	45 degrees
Corner chamfer angle	45 degrees
Series	HOLEX Pro Steel
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Helix angle characteristic	unequal spacing
Spacing of the cutters	unequal spacing
Cutting width a_e for milling operation	0.4×D for side milling
Cutting width a_e for milling operation	Full slot cutting depth 1×D
Through-coolant	no
Machining strategy	HPC
Colour ring	green
Type of product	End mill