

Garant

Solid carbide end mill HPC, ZOx, Ø f8 DC: 10 mm



Order data

Order number	202549 10
GTIN	4045197454270
Item class	11X

Description

Version:

Sturdy roughing slot drills **without** knuckle profile.

With strong core, **special chip breaker recesses** and **large polished flutes**.

Application:

For roughing milling with high demands on the component surface.

Tolerance nominal Ø: f8

No. of teeth Z: 4

Helix angle: 45 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HA to h6

Balance quality with shank: G 2.5 with HA

No. of teeth Z: 4

Flute length L_c : 30 mm

Overhang length L_1 incl. recess: 38 mm

Recess Ø D_1 : 9.2 mm

Overall length L: 80 mm

Shank Ø D_s : 10 mm

Technical description

Shank form	HA
Feed f_z for side milling in short-chipping aluminium	0.11 mm
Corner chamfer width at 45°	0.2 mm
Overhang length L_1 incl. recess	38 mm
Recess Ø D_1	9.2 mm

No. of teeth Z	4
Cutting edge $\varnothing D_c$	10 mm
Feed f_z for slot milling in short-chipping aluminium	0.09 mm
Shank $\varnothing D_s$	10 mm
Overall length L	80 mm
Flute length L_c	30 mm
Direction of infeed	horizontal, oblique and vertical
Shank	DIN 6535 HA to h6
Tolerance nominal \varnothing	f8
Balance quality with shank	G 2.5 with HA
Helix angle	45 degrees
Corner chamfer angle	45 degrees
Coating	ZOX
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	W
Helix angle characteristic	unequal spacing
Spacing of the cutters	unequal spacing
Cutting width a_e for milling operation	$0.3 \times D$ for side milling
Through-coolant	no
Machining strategy	HPC
Colour ring	yellow
Type of product	End mill

Services

Shank recess Type FRST	209900 FRST
Shank grinding Type HB	129100 HB