

Garant
Solid carbide milling cutter, TiAlN, Ø e8 DC: 3 mm

Order data

Order number	202555 3
GTIN	4045197117403
Item class	11X

Description
Version:

Double relief ground side clearance angle.
 Through-coolant: no
 Tolerance nominal Ø: e8
 No. of teeth Z: 4
 Helix angle: 30 degrees
 Direction of infeed: horizontal, oblique and vertical
 Shank: DIN 6535 HA to h6
 No. of teeth Z: 4
 Flute length L_c : 5 mm
 Overall length L: 32 mm
 Shank Ø D_s : 3 mm
 Shank form: HA
 Corner chamfer width at 45°: 0.04 mm

Technical description

Shank form	HA
Cutting edge Ø D_c	3 mm
Feed f_z for side milling in steel < 900 N/mm ²	0.011 mm
No. of teeth Z	4
Feed f_z for slot milling in steel < 900 N/mm ²	0.01 mm
Corner chamfer width at 45°	0.04 mm

Shank $\varnothing D_s$	3 mm
Overall length L	32 mm
Flute length L_c	5 mm
Direction of infeed	horizontal, oblique and vertical
Shank	DIN 6535 HA to h6
Tolerance nominal \varnothing	e8
Helix angle	30 degrees
Corner chamfer angle	45 degrees
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Cutting width a_e for milling operation	0.3×D for side milling
Cutting width a_e for milling operation	Full slot cutting depth 1×D
Through-coolant	no
Colour ring	without
Type of product	End mill