

**Garant**
**Solid carbide milling cutter, TiAlN, Ø e8 DC: 5 mm**

**Order data**

Order number	202555 5
GTIN	4045197117427
Item class	11X

**Description**
**Version:**

Double relief ground side clearance angle.  
 Through-coolant: no  
 Tolerance nominal Ø: e8  
 No. of teeth Z: 4  
 Helix angle: 30 degrees  
 Direction of infeed: horizontal, oblique and vertical  
 Shank: DIN 6535 HA to h6  
 No. of teeth Z: 4  
 Flute length  $L_c$ : 9 mm  
 Overall length L: 45 mm  
 Shank Ø  $D_s$ : 5 mm  
 Shank form: HA  
 Corner chamfer width at 45°: 0.06 mm

**Technical description**

Corner chamfer width at 45°	0.06 mm
No. of teeth Z	4
Feed $f_z$ for side milling in steel < 900 N/mm <sup>2</sup>	0.023 mm
Feed $f_z$ for slot milling in steel < 900 N/mm <sup>2</sup>	0.02 mm
Shank form	HA
Cutting edge Ø $D_c$	5 mm

Shank $\varnothing D_s$	5 mm
Overall length L	45 mm
Flute length $L_c$	9 mm
Direction of infeed	horizontal, oblique and vertical
Shank	DIN 6535 HA to h6
Tolerance nominal $\varnothing$	e8
Helix angle	30 degrees
Corner chamfer angle	45 degrees
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Cutting width $a_e$ for milling operation	0.3xD for side milling
Cutting width $a_e$ for milling operation	Full slot cutting depth 1xD
Through-coolant	no
Colour ring	without
Type of product	End mill