



Solid carbide milling cutter, TiAlN, Ø e8 DC: 10 mm

Order data

Order number	202610 10
GTIN	4045197117540
Item class	12X

Description
Version:

Eccentric relief ground.
 Through-coolant: no
 Tolerance nominal Ø: e8
 No. of teeth Z: 4
 Helix angle: 30 degrees
 Direction of infeed: horizontal, oblique and vertical
 Shank: DIN 6535 HB to h6
 No. of teeth Z: 4
 Flute length L_c : 14 mm
 Overall length L: 65 mm
 Shank Ø D_s : 10 mm
 Shank form: HB
 Feed f_z for slot milling in steel < 900 N/mm²: 0.05 mm

Technical description

Cutting edge Ø D_c	10 mm
No. of teeth Z	4
Feed f_z for slot milling in steel < 900 N/mm ²	0.05 mm
Shank form	HB
Feed f_z for side milling in steel < 900 N/mm ²	0.06 mm
Shank Ø D_s	10 mm

Overall length L	65 mm
Flute length L _c	14 mm
Direction of infeed	horizontal, oblique and vertical
Shank	DIN 6535 HB to h6
Tolerance nominal Ø	e8
Helix angle	30 degrees
Corner chamfer angle	90 degrees
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Cutting width a _e for milling operation	0.3×D for side milling
Cutting width a _e for milling operation	Full slot cutting depth 1×D
Through-coolant	no
Colour ring	without
Type of product	End mill

Services

Shank recess Type FRST	209900 FRST
------------------------	-------------