

Garant
Solid carbide milling cutter, TiAlN, Ø e8 DC: 15 mm

Order data

Order number	202725 15
GTIN	4045197746528
Item class	11X

Description
Version:

Double relief ground side clearance angle.

Without 45° cutting edge chamfer.

Through-coolant: no

No. of teeth Z: 4

Helix angle: 30 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HA to h6

No. of teeth Z: 4

Flute length L_c : 25 mm

Overhang length L_1 incl. recess: 35 mm

Recess Ø D_1 : 14.8 mm

Overall length L: 75 mm

Shank Ø D_s : 15 mm

Technical description

Feed f_z for slot milling in steel < 900 N/mm ²	0.06 mm
Overhang length L_1 incl. recess	35 mm
Flute length L_c	25 mm
Cutting edge Ø D_c	15 mm
Shank	DIN 6535 HA to h6
Direction of infeed	horizontal, oblique and vertical
Shank form	HA

No. of teeth Z	4
Recess $\varnothing D_1$	14.8 mm
Overall length L	75 mm
Feed f_z for side milling in steel < 900 N/mm ²	0.08 mm
Shank $\varnothing D_s$	15 mm
Helix angle	30 degrees
Corner chamfer angle	90 degrees
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	H
Cutting width a_e for milling operation	0.3×D for side milling
Cutting width a_e for milling operation	Full slot cutting depth 1×D
Through-coolant	no
Colour ring	without
Type of product	End mill