

Garant
GARANT Master INOX solid carbide milling cutter HPC, TiAlN, Ø h10 DC: 3 mm

Order data

Order number	202998 3
GTIN	4045197860910
Item class	11X

Description
Version:

For **roughing and finishing**.

HPC milling cutter with **newly developed high-performance coating** for **outstanding tool life** and **optimum metal removal rate** in a very wide range of stainless steels. **Greater oxidation resistance** and **high-temperature hardness**.

Can be used at **high cutting speeds**, particularly suitable even for TOOLOX®.

Advantage:

Particularly low vibration running.

Tolerance nominal Ø: h10

No. of teeth Z: 4

Helix angle: 40 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HB to h6

No. of teeth Z: 4

Flute length L_c : 5 mm

Overall length L: 50 mm

Shank Ø D_s : 6 mm

Corner chamfer width at 45°: 0.15 mm

Feed f_z for slot milling in stainless steel > 900 N/mm²: 0.012 mm

Technical description

Shank Ø D_s	6 mm
Flute length L_c	5 mm
Feed f_z for side milling in INOX > 900 N/mm ²	0.015 mm

Tolerance nominal \varnothing	h10
Feed f_z for slot milling in stainless steel $> 900 \text{ N/mm}^2$	0.012 mm
Overall length L	50 mm
No. of teeth Z	4
Corner chamfer width at 45°	0.15 mm
Shank	DIN 6535 HB to h6
Cutting edge $\varnothing D_c$	3 mm
Direction of infeed	horizontal, oblique and vertical
Helix angle	40 degrees
Corner chamfer angle	45 degrees
Series	GARANT Master INOX
Coating	TiAlN
Tool material	Solid carbide
Standard	DIN 6527
Type	N
Helix angle characteristic	unequal spacing
Spacing of the cutters	unequal spacing
Cutting width a_e for milling operation	Full slot cutting depth $1 \times D$
Cutting width a_e for milling operation	$0.3 \times D$ for side milling
Through-coolant	no
Machining strategy	HPC
Colour ring	blue
Type of product	End mill