

Garant
Solid carbide milling cutter HPC, TiAlN, Ø DC: 20M mm

Order data

Order number	203009 20M
GTIN	4045197657244
Item class	11X

Description
Version:

Specially for **machining stainless steels such as duplex steels at high rates of metal removal.**

Cutting edge chamfer: Size 4 = 0.07mm; size 5 – 8 = 0.12 mm; size 10 – 18 = 0.2 mm; ≥ size 20 = 0.3 mm

Tolerance nominal Ø: h10

No. of teeth Z: 4

Helix angle: 38 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HB to h6

No. of teeth Z: 4

Flute length L_c : 60 mm

Overhang length L_1 incl. recess: 70 mm

Recess Ø D_1 : 19.5 mm

Overall length L: 126 mm

Shank Ø D_s : 20 mm

Technical description

Feed f_z for slot milling in stainless steel > 900 N/mm ²	0.07 mm
Cutting edge Ø D_c	20 mm
Recess Ø D_1	19.5 mm
Corner chamfer width at 45°	0.3 mm
Feed f_z for side milling in INOX > 900 N/mm ²	0.1 mm
No. of teeth Z	4

Overhang length L_1 incl. recess	70 mm
Shank $\varnothing D_s$	20 mm
Overall length L	126 mm
Flute length L_c	60 mm
Direction of infeed	horizontal, oblique and vertical
Shank	DIN 6535 HB to h6
Tolerance nominal \varnothing	h10
Helix angle	38 degrees
Corner chamfer angle	45 degrees
Coating	TiAlN
Tool material	Solid carbide
Standard	DIN 6527
Type	N
Helix angle characteristic	unequal spacing
Spacing of the cutters	unequal spacing
Cutting width a_e for milling operation	0.3×D for side milling
Cutting width a_e for milling operation	Full slot cutting depth 1×D
Through-coolant	no
Machining strategy	HPC
Colour ring	blue
Type of product	End mill

Services

Shank recess Type FRST	209900 FRST
Shank clamping flats for shrink-fit chucks, with retainer function Shank \varnothing tool 20 mm	SZ2025 20