



Solid carbide milling cutter HPC, TiSi, Ø f8 DC: 16 mm



Order data

| | |
|--------------|---------------|
| Order number | 203014 16 |
| GTIN | 4045197551030 |
| Item class | 12X |

Description

Version:

Special TiSi coating.

Note:

NEW GENERATION AVAILABLE!

Recommended successor products are No. 203013, 203015, 203021, 203027.

Tolerance nominal Ø: f8

No. of teeth Z: 4

Helix angle: 35 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HB to h6

No. of teeth Z: 4

Flute length L_c : 36 mm

Overhang length L_1 incl. recess: 42 mm

Recess Ø D_1 : 15.5 mm

Overall length L: 92 mm

Shank Ø D_s : 16 mm

Technical description

| | |
|--|---------|
| Cutting edge Ø D_c | 16 mm |
| No. of teeth Z | 4 |
| Corner chamfer width at 45° | 0.3 mm |
| Feed f_z for slot milling in stainless steel > 900 N/mm ² | 0.05 mm |
| Overhang length L_1 incl. recess | 42 mm |

| | |
|---|----------------------------------|
| Feed f_z for side milling in INOX > 900 N/mm ² | 0.055 mm |
| Recess $\varnothing D_1$ | 15.5 mm |
| Shank $\varnothing D_s$ | 16 mm |
| Overall length L | 92 mm |
| Flute length L_c | 36 mm |
| Direction of infeed | horizontal, oblique and vertical |
| Shank | DIN 6535 HB to h6 |
| Tolerance nominal \varnothing | f8 |
| Helix angle | 35 degrees |
| Corner chamfer angle | 45 degrees |
| Coating | TiSi |
| Tool material | Solid carbide |
| Standard | Manufacturer's standard |
| Type | N |
| Helix angle characteristic | unequal spacing |
| Spacing of the cutters | unequal spacing |
| Cutting width a_e for milling operation | 0.3×D for side milling |
| Cutting width a_e for milling operation | Full slot cutting depth 1×D |
| Through-coolant | no |
| Machining strategy | HPC |
| Colour ring | blue |
| Type of product | End mill |

Services

| | |
|---|-------------|
| Shank recess Type FRST | 209900 FRST |
| Shank clamping flats for shrink-fit chucks, with retainer function Shank \varnothing tool 16 mm | SZ2025 16 |