



HOLEX Pro INOX solid carbide milling cutter HPC, AlCrN, Ø f8 DC: 8 mm

Order data

Order number	203015 8
GTIN	4045197772893
Item class	12X

Description
Version:

HPC milling cutters with **newly developed high-performance coating** for **outstanding tool working life** and **optimum metal removal rates** in a wide range of stainless steels. For use at **high cutting speeds**, particularly suitable even for steels up to approx. 1100 N/mm².

Tolerance nominal Ø: f8

No. of teeth Z: 4

Helix angle: 35 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HB to h6

No. of teeth Z: 4

Flute length L_c: 21 mm

Overhang length L₁ incl. recess: 25 mm

Recess Ø D₁: 7.7 mm

Overall length L: 63 mm

Shank Ø D_s: 8 mm

Technical description

Corner chamfer width at 45°	0.2 mm
Feed f _z for side milling in INOX > 900 N/mm ²	0.04 mm
Shank Ø D _s	8 mm
Flute length L _c	21 mm
Recess Ø D ₁	7.7 mm
Overall length L	63 mm

Tolerance nominal \varnothing	f8
Cutting edge $\varnothing D_c$	8 mm
Feed f_z for slot milling in stainless steel $> 900 \text{ N/mm}^2$	0.025 mm
Direction of infeed	horizontal, oblique and vertical
Shank	DIN 6535 HB to h6
No. of teeth Z	4
Overhang length L_1 incl. recess	25 mm
Helix angle	35 degrees
Corner chamfer angle	45 degrees
Series	HOLEX Pro INOX
Coating	AlCrN
Tool material	solid carbide
Standard	DIN 6527
Type	N
Helix angle characteristic	unequal spacing
Spacing of the cutters	unequal spacing
Cutting width a_e for milling operation	$0.4 \times D$ for side milling
Cutting width a_e for milling operation	Full slot cutting depth $1 \times D$
Through-coolant	no
Machining strategy	HPC
Colour ring	blue
Type of product	End mill