

Garant
Solid carbide milling cutter with chip separators TPC, TiAlN, Ø f8 DC: 8 mm

Order data

Order number	203019 8
GTIN	4045197609748
Item class	11X

Description
Version:

High-performance mills for machining stainless steels, **especially designed for TPC applications.**
Strengthened core.

Note:

$h_{m \max}$: The values stated in the table are maximum values.

$a_{e \max} = 0.08 \times D$ for TPC machining.

NEW GENERATION AVAILABLE!

Recommended successor product is No. 203103

Tolerance nominal Ø: f8

No. of teeth Z: 5

Helix angle: 45 degrees

Direction of infeed: horizontal and oblique

Shank: DIN 6535 HB to h6

Balance quality with shank: G 2.5 with HB

No. of teeth Z: 5

Flute length L_c : 24 mm

Overhang length L_1 incl. recess: 30 mm

Recess Ø D_1 : 7.8 mm

Overall length L: 68 mm

Shank Ø D_s : 8 mm

Technical description

Cutting edge Ø D_c	8 mm
Average chip thickness h_{\max} for TPC milling in INOX > 900 N/mm ²	0.04 mm

No. of teeth Z	5
Average chip thickness h_{\max} for TPC milling in INOX < 900 N/mm ²	0.05 mm
Overhang length L_1 incl. recess	30 mm
Recess $\varnothing D_1$	7.8 mm
Corner chamfer width at 45°	0.16 mm
Shank $\varnothing D_s$	8 mm
Overall length L	68 mm
Flute length L_c	24 mm
Direction of infeed	horizontal and oblique
Shank	DIN 6535 HB to h6
Tolerance nominal \varnothing	f8
Balance quality with shank	G 2.5 with HB
Helix angle	45 degrees
Corner chamfer angle	45 degrees
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Helix angle characteristic	unequal spacing
Spacing of the cutters	unequal spacing
Cutting width a_e for milling operation	0.08×D
Through-coolant	no
Machining strategy	TPC
Colour ring	blue
Type of product	End mill

Services

Shank recess Type FRST	209900 FRST
------------------------	-------------

