

Garant
Solid carbide milling cutter HPC / TPC, TiAlN, Ø e8 DC: 6 mm

Order data

Order number	203023 6
GTIN	4045197857576
Item class	11X

Description
Version:

Shank **similar to DIN 6535 HB.**

Note:

Successor product to No. 203018.

Tolerance nominal Ø: e8

No. of teeth Z: 4

Helix angle: 38 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HB to h6

No. of teeth Z: 4

Flute length L_c : 32 mm

Overall length L: 80 mm

Shank Ø D_s : 6 mm

Corner chamfer width at 45°: 0.4 mm

Feed f_z for side milling in INOX > 900 N/mm²: 0.04 mm

Technical description

Direction of infeed	horizontal, oblique and vertical
Tolerance nominal Ø	e8
Overall length L	80 mm
Cutting edge Ø D_c	6 mm
No. of teeth Z	4
Flute length L_c	32 mm

Corner chamfer width at 45°	0.4 mm
Shank $\varnothing D_s$	6 mm
Shank	DIN 6535 HB to h6
Feed f_z for side milling in INOX > 900 N/mm ²	0.04 mm
Helix angle	38 degrees
Corner chamfer angle	45 degrees
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Helix angle characteristic	unequal spacing
Spacing of the cutters	unequal spacing
Cutting width a_e for milling operation	0.04×D
Through-coolant	no
Machining strategy	HPC
Machining strategy	TPC
Colour ring	blue
Type of product	End mill