

Garant
Solid carbide milling cutter HPC / TPC, TiAlN, Ø e8 DC: 8 mm

Order data

Order number	203023 8
GTIN	4045197857583
Item class	11X

Description
Version:

Shank **similar to DIN 6535 HB.**

Note:

Successor product to No. 203018.

Tolerance nominal Ø: e8

No. of teeth Z: 4

Helix angle: 38 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HB to h6

No. of teeth Z: 4

Flute length L_c : 32 mm

Overall length L: 90 mm

Shank Ø D_s : 8 mm

Corner chamfer width at 45°: 0.4 mm

Feed f_z for side milling in INOX > 900 N/mm²: 0.04 mm

Technical description

Corner chamfer width at 45°	0.4 mm
Direction of infeed	horizontal, oblique and vertical
No. of teeth Z	4
Tolerance nominal Ø	e8
Flute length L_c	32 mm
Shank Ø D_s	8 mm

Overall length L	90 mm
Feed f_z for side milling in INOX > 900 N/mm ²	0.04 mm
Shank	DIN 6535 HB to h6
Cutting edge $\varnothing D_c$	8 mm
Helix angle	38 degrees
Corner chamfer angle	45 degrees
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Helix angle characteristic	unequal spacing
Spacing of the cutters	unequal spacing
Cutting width a_e for milling operation	0.04×D
Through-coolant	no
Machining strategy	HPC
Machining strategy	TPC
Colour ring	blue
Type of product	End mill