

Garant
Solid carbide milling cutter HPC, TiAlN, Ø e8 DC: 16 mm

Order data

Order number	203026 16
GTIN	4045197857996
Item class	11X

Description
Note:
Successor product to No. 203025.

Tolerance nominal Ø: e8
 No. of teeth Z: 4
 Helix angle: 38 degrees
 Direction of infeed: horizontal, oblique and vertical
 Shank: DIN 6535 HB to h6
 No. of teeth Z: 4
 Flute length L_c : 32 mm
 Overhang length L_1 incl. recess: 100 mm
 Recess Ø D_1 : 15 mm
 Overall length L: 150 mm
 Shank Ø D_s : 16 mm

Technical description

Overhang length L_1 incl. recess	100 mm
Recess Ø D_1	15 mm
Tolerance nominal Ø	e8
Feed f_z for side milling in INOX > 900 N/mm ²	0.08 mm
Flute length L_c	32 mm
Direction of infeed	horizontal, oblique and vertical
Overall length L	150 mm
Shank Ø D_s	16 mm

Corner chamfer width at 45°	0.5 mm
Shank	DIN 6535 HB to h6
Cutting edge $\varnothing D_c$	16 mm
No. of teeth Z	4
Helix angle	38 degrees
Corner chamfer angle	45 degrees
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Helix angle characteristic	unequal spacing
Spacing of the cutters	unequal spacing
Cutting width a_e for milling operation	0.1×D for side milling
Through-coolant	no
Machining strategy	HPC
Colour ring	blue
Type of product	End mill

Services

Shank clamping flats for shrink-fit chucks, with retainer function Shank \varnothing tool 16 mm

SZ2025 16