




## Solid carbide roughing end mill HPC, TiXSi, Ø f8 DC: 25 mm



### Order data

Order number	203044 25
GTIN	4045197679444
Item class	12X

### Description

#### Version:

For **roughing and finishing**.

Up to 1.5×D into solid material **at very high feed rates** with smooth cutting action.

#### Advantage:

Optimised flute form, eccentric relief ground, wide chip space.

Tolerance nominal Ø: f8

No. of teeth Z: 4

Helix angle: 38 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HB to h6

No. of teeth Z: 4

Flute length  $L_c$ : 68 mm

Overhang length  $L_1$  incl. recess: 78 mm

Recess Ø  $D_1$ : 24.5 mm

Overall length L: 136 mm

Shank Ø  $D_s$ : 25 mm

### Technical description

Overhang length $L_1$ incl. recess	78 mm
Corner chamfer width at 45°	0.3 mm
Feed $f_z$ for side milling in steel < 900 N/mm <sup>2</sup>	0.16 mm
Recess Ø $D_1$	24.5 mm
Cutting edge Ø $D_c$	25 mm

Feed $f_z$ for slot milling in steel $< 900 \text{ N/mm}^2$	0.12 mm
No. of teeth Z	4
Shank $\varnothing D_s$	25 mm
Overall length L	136 mm
Flute length $L_c$	68 mm
Direction of infeed	horizontal, oblique and vertical
Shank	DIN 6535 HB to h6
Tolerance nominal $\varnothing$	f8
Helix angle	38 degrees
Corner chamfer angle	45 degrees
Coating	TiXSi
Tool material	Solid carbide
Standard	DIN 6527
Type	N
Helix angle characteristic	unequal spacing
Spacing of the cutters	unequal spacing
Cutting width $a_e$ for milling operation	$0.3 \times D$ for side milling
Cutting width $a_e$ for milling operation	Full slot cutting depth $1 \times D$
Through-coolant	no
Machining strategy	HPC
Colour ring	green
Type of product	End mill

## Services

Shank recess Type FRST	209900 FRST
------------------------	-------------