



Solid carbide roughing end mill HPC, TiXSi, Ø DC: 16 mm



Order data

Order number	203047 16
GTIN	4045197679499
Item class	12X

Description

Version:

For **roughing and finishing**.

Up to $0.7 \times D$ into solid material **at very high feed rates** with smooth cutting action.

Without dynamic twist pitch.

Advantage:

Optimised flute form, eccentric relief ground, wide chip space.

Tolerance nominal \varnothing : f8

No. of teeth Z: 4

Helix angle: 38 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HB to h6

No. of teeth Z: 4

Flute length L_c : 48 mm

Overhang length L_1 incl. recess: 58 mm

Recess $\varnothing D_1$: 15.5 mm

Overall length L: 108 mm

Shank $\varnothing D_s$: 16 mm

Technical description

Overhang length L_1 incl. recess	58 mm
Corner chamfer width at 45°	0.3 mm
No. of teeth Z	4
Feed f_z for slot milling in steel $< 900 \text{ N/mm}^2$	0.08 mm
Feed f_z for side milling in steel $< 900 \text{ N/mm}^2$	0.1 mm

Recess $\varnothing D_1$	15.5 mm
Cutting edge $\varnothing D_c$	16 mm
Shank $\varnothing D_s$	16 mm
Overall length L	108 mm
Flute length L_c	48 mm
Direction of infeed	horizontal, oblique and vertical
Shank	DIN 6535 HB to h6
Tolerance nominal \varnothing	f8
Helix angle	38 degrees
Corner chamfer angle	45 degrees
Coating	TiXSi
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Spacing of the cutters	unequal spacing
Cutting width a_e for milling operation	0.25×D for side milling
Cutting width a_e for milling operation	Full slot cutting depth 1×D
Through-coolant	no
Machining strategy	HPC
Colour ring	green
Type of product	End mill

Services

Shank recess Type FRST	209900 FRST
Shank clamping flats for shrink-fit chucks, with retainer function Shank \varnothing tool 16 mm	SZ2025 16