

Solid carbide roughing end mill MTC, AlCrN, Ø e8 DC: 16 mm



Order data

Order number	203071 16
GTIN	4045197776099
Item class	11X

Description

Version:

For **roughing and finishing** up to 0.7×D into solid material **at very high feed rates** with smooth cutting action.

For cutting force reduction and better surface quality due to 45° helix.

Improved coating for a further reduction in cutting force combined with increased tool life.

Application:

Especially for MTC (Multi Task Cutting) use on the new generation of turning / milling centres.

Tolerance nominal Ø: e8

No. of teeth Z: 4

Helix angle: 45 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HB to h6

Balance quality with shank: G 2.5 with HB

No. of teeth Z: 4

Flute length L_c: 36 mm

Overhang length L₁ incl. recess: 100 mm

Recess \emptyset D₁: 15.5 mm Overall length L: 150 mm Shank \emptyset D_s: 16 mm

Technical description

Corner chamfer width at 45°	0.3 mm
Flute length L _c	36 mm
Tolerance nominal Ø	e8
Cutting edge \emptyset D _c	16 mm

0.05 mm
15.5 mm
16 mm
150 mm
horizontal, oblique and vertical
100 mm
0.065 mm
DIN 6535 HB to h6
G 2.5 with HB
4
45 degrees
45 degrees
AlCrN
solid carbide
Manufacturer's standard
N
unequal spacing
unequal spacing
0.1×D for side milling
Full slot cutting depth 1×D
no
MTC
green
End mill

Services

Shank clamping flats for shrink-fit chucks, with retainer
function Shank Ø tool 16 mm

SZ2025 16

