


Garant
Diabolo solid carbide milling cutter HPC, TiAlN, Ø e8 DC: 10 mm

Order data

Order number	203282 10
GTIN	4045197597502
Item class	11X

Description
Version:
GARANT Diabolo:

Special geometry, coating and carbide, specially for hard machining.

Application:

For profile milling as finishing.

(Plunge cutting only to shallow depths).

Tolerance nominal Ø: e8

No. of teeth Z: 6

Helix angle: 50 degrees

Direction of infeed: horizontal and oblique

Shank: DIN 6535 HA to h6

No. of teeth Z: 6

Flute length L_c : 30 mm

Overall length L: 85 mm

Shank Ø D_s : 10 mm

Feed f_z for side milling in steel < 65 HRC: 0.02 mm

Technical description

Feed f_z for side milling in steel < 65 HRC	0.02 mm
No. of teeth Z	6
Cutting edge Ø D_c	10 mm
Shank Ø D_s	10 mm
Overall length L	85 mm
Flute length L_c	30 mm

Direction of infeed	horizontal and oblique
Shank	DIN 6535 HA to h6
Tolerance nominal \varnothing	e8
Helix angle	50 degrees
Corner chamfer angle	90 degrees
Series	Diabolo
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	H
Helix angle characteristic	unequal spacing
Cutting width a_e for milling operation	$0.05 \times D$ for side milling
Through-coolant	no
Machining strategy	HPC
Colour ring	red
Type of product	End mill

Services

Shank recess Type FRST	209900 FRST
Shank grinding Type HB	129100 HB