


Garant
Diabolo solid carbide milling cutter HPC, TiAlN, Ø e8 DC: 20 mm

Order data

Order number	203282 20
GTIN	4045197597557
Item class	11X

Description
Version:
GARANT Diabolo:

Special geometry, coating and carbide, specially for hard machining.

Application:

For profile milling as finishing.

(Plunge cutting only to shallow depths).

Tolerance nominal Ø: e8

No. of teeth Z: 10

Helix angle: 50 degrees

Direction of infeed: horizontal and oblique

Shank: DIN 6535 HA to h6

No. of teeth Z: 10

Flute length L_c : 60 mm

Overall length L: 126 mm

Shank Ø D_s : 20 mm

Feed f_z for side milling in steel < 65 HRC: 0.03 mm

Technical description

No. of teeth Z	10
Feed f_z for side milling in steel < 65 HRC	0.03 mm
Cutting edge Ø D_c	20 mm
Shank Ø D_s	20 mm
Overall length L	126 mm
Flute length L_c	60 mm

Direction of infeed	horizontal and oblique
Shank	DIN 6535 HA to h6
Tolerance nominal \varnothing	e8
Helix angle	50 degrees
Corner chamfer angle	90 degrees
Series	Diabolo
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	H
Helix angle characteristic	unequal spacing
Cutting width a_e for milling operation	$0.05 \times D$ for side milling
Through-coolant	no
Machining strategy	HPC
Colour ring	red
Type of product	End mill

Services

Shank recess Type FRST	209900 FRST
Shank clamping flats for shrink-fit chucks, with retainer function Shank \varnothing tool 20 mm	SZ2025 20
Shank grinding Type HB	129100 HB