

Garant

Solid carbide milling cutter HPC / TPC, TiAlN, Ø DC: 16 mm



Order data

Order number	203373 16
GTIN	4045197641342
Item class	11X

Description

Version:

GARANT Diabolo 70:

Special solid carbide substrate with extremely high tensile strength combined with **outstanding wear resistance** for optimum process reliability. Newly developed **nano-crystalline high-tech coating for hard milling up to 70 HRC**. Very suitable for **continuous use** in tool and mould making.

Sizes 2 – 5: **Recess angle $\alpha = 15^\circ$.**

Tolerance:

- **Size nominal \varnothing : $D_c \leq$ size 12: 0 / -0.02 mm;**
- **Size nominal \varnothing : D_c from size 16: 0 / -0.03 mm.**

Application:

Due to the **special hard geometry** ideal for use on hardened materials from 60 HRC to 70 HRC.

For profile milling as a finishing operation.

(Plunge milling only to shallow depths).

Note:

For materials > 65 HRC: $a_e = 0.02 \times D$.

Tolerance nominal \varnothing : 0 / -0.03

No. of teeth Z: 6

Helix angle: 45 degrees

Direction of infeed: horizontal and oblique

Shank: DIN 6535 HA to h6

No. of teeth Z: 6

Flute length L_c : 66 mm

Overall length L: 130 mm

Shank $\varnothing D_s$: 16 mm

Feed f_z for side milling in steel < 70 HRC: 0.15 mm

Technical description

No. of teeth Z	6
Cutting edge $\varnothing D_c$	16 mm
Feed f_z for side milling in steel < 70 HRC	0.15 mm
Shank $\varnothing D_s$	16 mm
Overall length L	130 mm
Flute length L_c	66 mm
Direction of infeed	horizontal and oblique
Shank	DIN 6535 HA to h6
Tolerance nominal \varnothing	0 / -0.03
Helix angle	45 degrees
Corner chamfer angle	90 degrees
Series	Diabolo
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	H
Cutting width a_e for milling operation	$0.02 \times D$
Through-coolant	no
Machining strategy	TPC
Machining strategy	HPC
Colour ring	red
Type of product	End mill

Services

Shank recess Type FRST	209900 FRST
Shank clamping flats for shrink-fit chucks, with retainer function Shank \varnothing tool 16 mm	SZ2025 16
Shank grinding Type HB	129100 HB

