

Garant

Solid carbide milling cutter DIN 6535 HB, TiAlN, Ø e8 DC: 6 mm



Order data

Order number	203480 6
GTIN	4045197119544
Item class	11X

Description

Version:

High stability and **extremely smooth cutting action**

due to at least 6 teeth.

Double relief ground clearance angle.

Application:

For peripheral milling as a **finishing operation.**

Through-coolant: no

Tolerance nominal Ø: e8

No. of teeth Z: 6

Helix angle: 45 degrees

Direction of infeed: horizontal

Shank: DIN 6535 HB to h6

No. of teeth Z: 6

Flute length L_c : 13 mm

Overhang length L_1 incl. recess: 18 mm

Recess Ø D_1 : 5.8 mm

Overall length L: 57 mm

Shank Ø D_s : 6 mm

Technical description

Feed f_z for side milling in steel < 900 N/mm ²	0.054 mm
Overhang length L_1 incl. recess	18 mm
No. of teeth Z	6
Recess Ø D_1	5.8 mm

Corner chamfer width at 45°	0.05 mm
Cutting edge $\varnothing D_c$	6 mm
Shank $\varnothing D_s$	6 mm
Overall length L	57 mm
Flute length L_c	13 mm
Direction of infeed	horizontal
Shank	DIN 6535 HB to h6
Tolerance nominal \varnothing	e8
Helix angle	45 degrees
Corner chamfer angle	45 degrees
Coating	TiAlN
Tool material	Solid carbide
Standard	DIN 6527
Type	N
Cutting width a_e for milling operation	0.1×D for side milling
Through-coolant	no
Colour ring	green
Type of product	End mill

Services

Shank recess Type FRST	209900 FRST
------------------------	-------------