


Solid carbide milling cutter, TiAlN, Ø h10 DC: 6 mm

Order data

Order number	203510 6
GTIN	4045197964168
Item class	12X

Description
Version:

High stability and **extremely smooth cutting action** due to at least 6 teeth.

Eccentric relief ground.

Application:

For peripheral milling as a **finishing operation**.

Through-coolant: no

Tolerance nominal Ø: h10

No. of teeth Z: 6

Helix angle: 45 degrees

Direction of infeed: horizontal

Shank: DIN 6535 HA to h6

No. of teeth Z: 6

Flute length L_c : 13 mm

Overall length L: 57 mm

Shank Ø D_s : 6 mm

Corner chamfer width at 45°: 0.1 mm

Feed f_z for side milling in steel < 900 N/mm²: 0.054 mm

Technical description

Shank	DIN 6535 HA to h6
Tolerance nominal Ø	h10
Cutting edge Ø D_c	6 mm
Corner chamfer width at 45°	0.1 mm
Feed f_z for side milling in steel < 900 N/mm ²	0.054 mm

No. of teeth Z	6
Helix angle	45 degrees
Overall length L	57 mm
Flute length L _c	13 mm
Direction of infeed	horizontal
Shank Ø D _s	6 mm
Corner chamfer angle	45 degrees
Coating	TiAlN
Tool material	Solid carbide
Standard	DIN 6527
Type	N
Cutting width a _e for milling operation	0.1×D for side milling
Through-coolant	no
Colour ring	without
Type of product	End mill

Services

Shank grinding Type HB	129100 HB
------------------------	-----------