


Solid carbide milling cutter, TiAlN, Ø h10 DC: 5 mm

Order data

Order number	203520 5
GTIN	4045197119643
Item class	12X

Description
Version:

High stability and **extremely smooth cutting action**

due to at least 6 teeth.

Eccentric relief ground.

Application:

For peripheral milling as a **finishing operation**.

Through-coolant: no

Tolerance nominal Ø: h10

No. of teeth Z: 6

Helix angle: 45 degrees

Direction of infeed: horizontal

Shank: DIN 6535 HB to h6

No. of teeth Z: 6

Flute length L_c : 13 mm

Overall length L: 57 mm

Shank Ø D_s : 6 mm

Corner chamfer width at 45°: 0.1 mm

Feed f_z for side milling in steel < 900 N/mm²: 0.032 mm

Technical description

Cutting edge Ø D_c	5 mm
Corner chamfer width at 45°	0.1 mm
No. of teeth Z	6
Feed f_z for side milling in steel < 900 N/mm ²	0.032 mm

Shank $\varnothing D_s$	6 mm
Overall length L	57 mm
Flute length L_c	13 mm
Direction of infeed	horizontal
Shank	DIN 6535 HB to h6
Tolerance nominal \varnothing	h10
Helix angle	45 degrees
Corner chamfer angle	45 degrees
Coating	TiAlN
Tool material	Solid carbide
Standard	DIN 6527
Type	N
Cutting width a_e for milling operation	0.1×D for side milling
Through-coolant	no
Colour ring	without
Type of product	End mill