

Garant
Solid carbide high precision milling cutter, TiAlN, Ø f8 DC: 25 mm

Order data

Order number	203540 25
GTIN	4045197509949
Item class	11X

Description
Version:

High stability and **extremely smooth cutting action** due to at least 6 teeth. **Eccentric relief ground.**

With maximum 0.003 mm tapering.

Extremely **high taper accuracy with tolerances in the µm range**, for **precise 90° angles** and plane-parallel surfaces in profile milling.

For the most demanding angular accuracy.

Cutter corner chamfer undefined due to eccentric relief grinding.

Application:

For peripheral milling as a **finishing operation.**

Tolerance nominal Ø: f8

No. of teeth Z: 8

Helix angle: 45 degrees

Direction of infeed: horizontal

Shank: DIN 6535 HA to h6

Balance quality with shank: G 2.5 with HA

No. of teeth Z: 8

Flute length L_c : 105 mm

Overall length L: 165 mm

Shank Ø D_s : 25 mm

Feed f_z for side milling in steel < 900 N/mm²: 0.12 mm

Technical description

Cutting edge Ø D_c	25 mm
Feed f_z for side milling in steel < 900 N/mm ²	0.12 mm

No. of teeth Z	8
Shank $\varnothing D_s$	25 mm
Overall length L	165 mm
Flute length L_c	105 mm
Direction of infeed	horizontal
Shank	DIN 6535 HA to h6
Tolerance nominal \varnothing	f8
Balance quality with shank	G 2.5 with HA
Helix angle	45 degrees
Corner chamfer angle	90 degrees
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Helix angle characteristic	unequal spacing
Spacing of the cutters	unequal spacing
Milling application	Mono milling tools high-precision 90°
Cutting width a_e for milling operation	0.05×D for side milling
Through-coolant	no
Colour ring	green
Type of product	End mill

Services

Shank recess Type FRST	209900 FRST
Shank grinding Type HB	129100 HB