


Solid carbide milling cutter, TiAlN, Ø DC: 14 mm

Order data

Order number	203617 14
GTIN	4045197958747
Item class	12X

Description
Version:

For **finishing operations**. Special geometry for optimum chip evacuation. For **profile milling as a finishing operation**. Very sturdy version with strengthened core.

Through-coolant: no

Tolerance nominal Ø: h10

No. of teeth Z: 6

Helix angle: 45 degrees

Direction of infeed: horizontal

Shank: DIN 6535 HA to h6

No. of teeth Z: 6

Flute length L_c : 18 mm

Overall length L: 75 mm

Shank Ø D_s : 14 mm

Feed f_z for side milling in steel < 900 N/mm²: 0.085 mm

Technical description

Direction of infeed	horizontal
Shank	DIN 6535 HA to h6
Cutting edge Ø D_c	14 mm
Helix angle	45 degrees
Feed f_z for side milling in steel < 900 N/mm ²	0.085 mm
No. of teeth Z	6
Overall length L	75 mm

Tolerance nominal \varnothing	h10
Flute length L_c	18 mm
Shank $\varnothing D_s$	14 mm
Corner chamfer angle	90 degrees
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Cutting width a_e for milling operation	0.1×D for side milling
Through-coolant	no
Colour ring	without
Type of product	End mill

Services

Shank clamping flats for shrink-fit chucks, with retainer function Shank \varnothing tool 20 mm

SZ2025 20