

Garant

GARANT Master Steel solid carbide finishing cutter HPC, TiAlN, Ø f8 DC: 10 mm



Order data

Order number	204012 10
GTIN	4045197886613
Item class	11X

Description

Version:

For **finishing operations**.

Special geometry for optimum chip evacuation.

Unequal spacing gives high **intrinsic stability and smooth cutting action**.

For **profile milling as a finishing operation**.

Note:

$$a_{e\max} = 0.1 \times D$$

Can be reground from $\varnothing D_c = 6$ mm.

Tolerance nominal \varnothing : f8

No. of teeth Z: 7

Helix angle: 45 degrees

Direction of infeed: horizontal

Shank: DIN 6535 HA to h6

Balance quality with shank: G 2.5 with HA

No. of teeth Z: 7

Flute length L_c : 22 mm

Overall length L: 72 mm

Shank $\varnothing D_s$: 10 mm

Corner chamfer width at 45°: 0.1 mm

Feed f_z for side milling in steel < 900 N/mm²: 0.081 mm

Technical description

Direction of infeed	horizontal
Corner chamfer width at 45°	0.1 mm

Balance quality with shank	G 2.5 with HA
No. of teeth Z	7
Cutting edge $\varnothing D_c$	10 mm
Shank $\varnothing D_s$	10 mm
Overall length L	72 mm
Flute length L_c	22 mm
Tolerance nominal \varnothing	f8
Shank	DIN 6535 HA to h6
Feed f_z for side milling in steel < 900 N/mm ²	0.081 mm
Helix angle	45 degrees
Corner chamfer angle	45 degrees
Series	GARANT Master Steel
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Spacing of the cutters	unequal spacing
Cutting width a_e for milling operation	0.1×D for side milling
Through-coolant	no
Machining strategy	HPC
Colour ring	green
Type of product	End mill

Services

Shank grinding Type HB

129100 HB