


Garant
GARANT Master Steel solid carbide finishing cutter HPC, TiAlN, Ø f8 DC: 16 mm

Order data

Order number	204015 16
GTIN	4045197954541
Item class	11X

Description
Version:

For **finishing operations**.

Special geometry for optimum chip evacuation.

Unequal spacing gives high **intrinsic stability and smooth cutting action**.

For **profile milling as a finishing operation**.

Note:

Can be reground from $\varnothing D_c = 6$ mm.

$$a_{e\max} = 0.1 \times D$$

Tolerance nominal \varnothing : f8

No. of teeth Z: 7

Helix angle: 45 degrees

Direction of infeed: horizontal

Shank: DIN 6535 HA to h6

Balance quality with shank: G 2.5 with HA

No. of teeth Z: 7

Flute length L_c : 48 mm

Overall length L: 108 mm

Shank $\varnothing D_s$: 16 mm

Feed f_z for side milling in steel < 900 N/mm²: 0.117 mm

Technical description

Cutting edge $\varnothing D_c$	16 mm
Feed f_z for side milling in steel < 900 N/mm ²	0.117 mm
Balance quality with shank	G 2.5 with HA

Tolerance nominal \varnothing	f8
Overall length L	108 mm
Shank $\varnothing D_s$	16 mm
Helix angle	45 degrees
No. of teeth Z	7
Shank	DIN 6535 HA to h6
Direction of infeed	horizontal
Flute length L_c	48 mm
Corner chamfer angle	90 degrees
Series	GARANT Master Steel
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Spacing of the cutters	unequal spacing
Cutting width a_e for milling operation	$0.1 \times D$ for side milling
Through-coolant	no
Machining strategy	HPC
Colour ring	green
Type of product	End mill

Services

Shank clamping flats for shrink-fit chucks, with retainer function Shank \varnothing tool 16 mm	SZ2025 16
Shank grinding Type HB	129100 HB