

Garant
Solid carbide roughing slot drill with internal coolant supply, DLC, Ø d11 DC: 8 mm

Order data

Order number	205336 8
GTIN	4045197767271
Item class	11X

Description
Version:

Dimensions similar to DIN 6527.

Knuckle form profile.

Special profile for machining non-ferrous metals.

With through-coolant.

With the latest generation of **DLC coating sp²**.

Through-coolant: yes

Tolerance nominal Ø: d11

No. of teeth Z: 3

Helix angle: 30 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HA to h6

No. of teeth Z: 3

Flute length L_c: 16 mm

Overhang length L₁ incl. recess: 27 mm

Recess Ø D₁: 7.8 mm

Overall length L: 63 mm

Shank Ø D_s: 8 mm

Technical description

Recess Ø D ₁	7.8 mm
Cutting edge Ø D _c	8 mm
No. of teeth Z	3

Feed f_z for side milling in short-chipping aluminium	0.08 mm
Feed f_z for slot milling in short-chipping aluminium	0.06 mm
Shank	DIN 6535 HA to h6
Overall length L	63 mm
Tolerance nominal \varnothing	d11
Direction of infeed	horizontal, oblique and vertical
Flute length L_c	16 mm
Overhang length L_1 incl. recess	27 mm
Corner chamfer width at 45°	0.45 mm
Shank $\varnothing D_s$	8 mm
Helix angle	30 degrees
Corner chamfer angle	45 degrees
Coating	DLC
Tool material	solid carbide
Standard	Manufacturer's standard
Milling profile	WR
Cutting width a_e for milling operation	0.5×D for side milling
Cutting width a_e for milling operation	Full slot cutting depth 1×D
Through-coolant	yes
Colour ring	yellow
Type of product	End mill

Services

Shank clamping flats for shrink-fit chucks, with retainer function Shank \varnothing tool 12 mm	SZ2025 12
Shank grinding Type HB	129100 HB