


Garant
GARANT Master Steel SlotMachine solid carbide roughing end mill HPC, TiAlN, Ø d11 DC: 14 mm

Order data

Order number	205548 14
GTIN	4045197853578
Item class	11X

Description
Version:

With a new-type knurled profile, optimised for higher feed rates. Improved cutting edge protection thanks to slight edge honing. Tremendous bending strength due to the use of ultra-fine grain substrate.

Feed rate per tooth up to 0.1 mm up to a depth of 2×D (in the slot milled from solid).

Advantage:

The tool geometry produces particularly tightly rolled swarf that is discharged via flat chip breaker recesses. As a result, the tool maintains an extremely stable core. Plunge angle of up to 10° possible thanks to generous recess on the front face.

Application:

For roughing machining, particularly suitable for full-slot machining.

Tolerance nominal Ø: d11

No. of teeth Z: 5

Helix angle: 42 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HB to h6

No. of teeth Z: 5

Flute length L_c : 18 mm

Overall length L: 75 mm

Shank Ø D_s : 14 mm

Corner chamfer width at 45°: 0.7 mm

Feed f_z for slot milling in steel < 900 N/mm²: 0.08 mm

Technical description

Direction of infeed	horizontal, oblique and vertical
---------------------	----------------------------------

Feed f_z for slot milling in steel < 900 N/mm ²	0.08 mm
Shank	DIN 6535 HB to h6
Flute length L_c	18 mm
Feed f_z for side milling in steel < 900 N/mm ²	0.1 mm
Shank $\varnothing D_s$	14 mm
Overall length L	75 mm
Cutting edge $\varnothing D_c$	14 mm
Tolerance nominal \varnothing	d11
Corner chamfer width at 45°	0.7 mm
No. of teeth Z	5
Helix angle	42 degrees
Corner chamfer angle	45 degrees
Series	GARANT Master Steel
Coating	TiAlN
Tool material	Solid carbide
Standard	DIN 6527
Milling profile	NR
Spacing of the cutters	unequal spacing
Cutting width a_e for milling operation	0.5×D for side milling
Cutting width a_e for milling operation	Full slot cutting depth 1×D
Through-coolant	no
Machining strategy	HPC
Colour ring	green
Type of product	End mill