Garant

GARANT Master Steel SlotMachine solid carbide roughing end mill HPC, TiAIN, Ø d11 DC: 4 mm



Order data

Order number	205548 4
GTIN	4045197853196
Item class	11X

Description

Version:

With a new-type knurled profile, optimised for higher feed rates. Improved cutting edge protection thanks to slight edge honing. Tremendous bending strength due to the use of ultra-fine grain substrate.

Feed rate per tooth up to 0.1 mm up to a depth of 2×D (in the slot milled from solid).

Advantage:

The tool geometry produces particularly tightly rolled swarf that is discharged via flat chip breaker recesses. As a result, the tool maintains an extremely stable core. Plunge angle of up to 10° possible thanks to generous recess on the front face.

Application:

For roughing machining, particularly suitable for full-slot machining. Tolerance nominal \emptyset : d11 No. of teeth Z: 5 Helix angle: 42 degrees Direction of infeed: horizontal, oblique and vertical Shank: DIN 6535 HB to h6 No. of teeth Z: 5 Flute length L_c: 8 mm Overall length L: 54 mm Shank \emptyset D_s: 6 mm Corner chamfer width at 45°: 0.2 mm Feed f_z for slot milling in steel < 900 N/mm²: 0.03 mm

Technical description

Overall length L

54 mm

Flute length L _c	8 mm
	0.03 mm
Feed f _z for slot milling in steel < 900 N/mm ²	
No. of teeth Z	5
Shank	DIN 6535 HB to h6
Shank \emptyset D _s	6 mm
Corner chamfer width at 45°	0.2 mm
Direction of infeed	horizontal, oblique and vertical
Tolerance nominal Ø	d11
Cutting edge $Ø D_c$	4 mm
Feed f_z for side milling in steel < 900 N/mm ²	0.04 mm
Helix angle	42 degrees
Corner chamfer angle	45 degrees
Series	GARANT Master Steel
Coating	TiAIN
Tool material	Solid carbide
Standard	DIN 6527
Milling profile	NR
Spacing of the cutters	unequal spacing
Cutting width a_e for milling operation	0.5×D for side milling
Cutting width a_e for milling operation	Full slot cutting depth 1×D
Through-coolant	no
Machining strategy	HPC
Colour ring	green
Type of product	End mill