

Garant
GARANT Master Steel SlotMachine solid carbide roughing end mill HPC, TiAlN, Ø d11 DC: 6 mm

Order data

Order number	205552 6
GTIN	4045197958952
Item class	11X

Description
Version:

With a new-type knurled profile, optimised for higher feed rates. Improved cutting edge protection thanks to slight edge honing. Tremendous bending strength due to the use of ultra-fine grain substrate.

Advantage:

The tool geometry produces particularly tightly rolled swarf that is discharged via flat chip breaker recesses. As a result, the tool maintains an extremely stable core. Plunge angle of up to 10° possible thanks to generous recess on the front face.

Application:

For roughing machining, particularly suitable for full-slot machining.

Tolerance nominal Ø: d11

No. of teeth Z: 5

Helix angle: 42 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HB to h6

No. of teeth Z: 5

Flute length L_c : 13 mm

Overhang length L_1 incl. recess: 25 mm

Recess Ø D_1 : 5.6 mm

Overall length L: 62 mm

Shank Ø D_s : 6 mm

Technical description

Overall length L	62 mm
------------------	-------

Feed f_z for side milling in steel < 900 N/mm ²	0.045 mm
Direction of infeed	horizontal, oblique and vertical
Shank	DIN 6535 HB to h6
Tolerance nominal \varnothing	d11
Cutting edge $\varnothing D_c$	6 mm
Helix angle	42 degrees
No. of teeth Z	5
Corner chamfer width at 45°	0.3 mm
Shank $\varnothing D_s$	6 mm
Flute length L_c	13 mm
Recess $\varnothing D_1$	5.6 mm
Feed f_z for slot milling in steel < 900 N/mm ²	0.035 mm
Overhang length L_1 incl. recess	25 mm
Corner chamfer angle	45 degrees
Series	GARANT Master Steel
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Milling profile	NR
Spacing of the cutters	unequal spacing
Cutting width a_e for milling operation	Full slot cutting depth 1×D
Cutting width a_e for milling operation	0.4×D for side milling
Through-coolant	no
Machining strategy	HPC
Colour ring	green
Type of product	End mill