

Garant

GARANT Master Steel SlotMachine solid carbide roughing end mill HPC / TPC, TiAlN, Ø d11 DC: 16 mm



Order data

Order number	205554 16
GTIN	4045197959980
Item class	11X

Description

Version:

With a new-type knurled profile, optimised for higher feed rates. Improved cutting edge protection thanks to slight edge honing. Tremendous bending strength due to the use of ultra-fine grain substrate.

Advantage:

The tool geometry produces particularly tightly rolled swarf that is discharged via flat chip breaker recesses. As a result, the tool maintains an extremely stable core.

Plunge angle of up to 10° possible thanks to generous recess on the front face.

Application:

For roughing machining.

Problem-solver for TPC machining.

Tolerance nominal Ø: d11

No. of teeth Z: 5

Helix angle: 42 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HB to h6

No. of teeth Z: 5

Flute length L_c : 48 mm

Overhang length L_1 incl. recess: 55 mm

Recess Ø D_1 : 14.8 mm

Overall length L: 108 mm

Shank Ø D_s : 16 mm

Technical description

Feed f_z for slot milling in steel < 900 N/mm ²	0.07 mm
--	---------

Overhang length L_1 incl. recess	55 mm
Recess $\varnothing D_1$	14.8 mm
Helix angle	42 degrees
Flute length L_c	48 mm
Direction of infeed	horizontal, oblique and vertical
Shank $\varnothing D_s$	16 mm
No. of teeth Z	5
Cutting edge $\varnothing D_c$	16 mm
Feed f_z for side milling in steel < 900 N/mm ²	0.09 mm
Overall length L	108 mm
Corner chamfer width at 45°	0.8 mm
Shank	DIN 6535 HB to h6
Tolerance nominal \varnothing	d11
Corner chamfer angle	45 degrees
Series	GARANT Master Steel
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Milling profile	NR
Spacing of the cutters	unequal spacing
Cutting width a_e for milling operation	Full slot cutting depth 1×D
Cutting width a_e for milling operation	0.4×D for side milling
Through-coolant	no
Machining strategy	HPC
Colour ring	green
Type of product	End mill