

## Garant

### Solid carbide roughing end mill MTC, TiAlN, Ø d11 DC: 25 mm



#### Order data

Order number	205714 25
GTIN	4045197362803
Item class	11X

#### Description

##### Version:

Dimensions similar to DIN 6527.

##### Optimised special knuckle profile for roughing.

Very **high rate of metal removal**.

##### Application:

Especially for **MTC (Multi Task Cutting)** use on the new generation of turning / milling centres.

Tolerance nominal Ø: d11

No. of teeth Z: 5

Helix angle: 45 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HB to h6

No. of teeth Z: 5

Flute length  $L_c$ : 50 mm

Overhang length  $L_1$  incl. recess: 65 mm

Recess Ø  $D_1$ : 24 mm

Overall length L: 125 mm

Shank Ø  $D_s$ : 25 mm

#### Technical description

Recess Ø $D_1$	24 mm
Feed $f_z$ for side milling in steel < 900 N/mm <sup>2</sup>	0.12 mm
Feed $f_z$ for slot milling in steel < 900 N/mm <sup>2</sup>	0.1 mm
Overhang length $L_1$ incl. recess	65 mm
Corner chamfer width at 45°	0.5 mm

Cutting edge $\varnothing D_c$	25 mm
No. of teeth Z	5
Shank $\varnothing D_s$	25 mm
Overall length L	125 mm
Flute length $L_c$	50 mm
Direction of infeed	horizontal, oblique and vertical
Shank	DIN 6535 HB to h6
Tolerance nominal $\varnothing$	d11
Helix angle	45 degrees
Corner chamfer angle	45 degrees
Coating	TiAlN
Tool material	Solid carbide
Standard	DIN 6527
Milling profile	HR
Cutting width $a_e$ for milling operation	0.5×D for side milling
Cutting width $a_e$ for milling operation	Full slot cutting depth 1×D
Through-coolant	no
Machining strategy	MTC
Colour ring	green
Type of product	End mill

## Services

Shank recess Type FRST	209900 FRST
------------------------	-------------