

Garant
Solid carbide roughing end mill MTC, TiAlN, Ø d11 DC: 16 mm

Order data

Order number	205718 16
GTIN	4045197362919
Item class	11X

Description
Version:

Dimensions similar to DIN 6527.

Optimised special knuckle profile for roughing.

Very high rate of metal removal.

Can be used as a **universal end mill**.

Application:

Especially for **MTC (Multi Task Cutting)** use on the new generation of turning / milling centres.

Tolerance nominal Ø: d11

No. of teeth Z: 5

Helix angle: 45 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HB to h6

No. of teeth Z: 5

Flute length L_c : 32 mm

Overhang length L_1 incl. recess: 100 mm

Recess Ø D_1 : 15.5 mm

Overall length L: 150 mm

Shank Ø D_s : 16 mm

Technical description

Cutting edge Ø D_c	16 mm
Feed f_z for side milling in steel < 900 N/mm ²	0.072 mm
Feed f_z for slot milling in steel < 900 N/mm ²	0.065 mm
Recess Ø D_1	15.5 mm

No. of teeth Z	5
Overhang length L_1 incl. recess	100 mm
Corner chamfer width at 45°	0.35 mm
Shank $\varnothing D_s$	16 mm
Overall length L	150 mm
Flute length L_c	32 mm
Direction of infeed	horizontal, oblique and vertical
Shank	DIN 6535 HB to h6
Tolerance nominal \varnothing	d11
Helix angle	45 degrees
Corner chamfer angle	45 degrees
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Milling profile	HR
Cutting width a_e for milling operation	0.1×D for side milling
Cutting width a_e for milling operation	Full slot cutting depth 1×D
Through-coolant	no
Machining strategy	MTC
Colour ring	green
Type of product	End mill

Services

Shank recess Type FRST	209900 FRST
Shank clamping flats for shrink-fit chucks, with retainer function Shank \varnothing tool 16 mm	SZ2025 16