


Garant
Solid carbide torus cutter, DLC, Ø e8 DC / R1: 12/4,0 mm

Order data

Order number	206065 12/4,0
GTIN	4045197766335
Item class	11X

Description
Version:

Tolerance: $R_1 = \pm 0.01 \text{ mm}$.

With the latest generation of **DLC coating sp²**.

With **double relief ground side clearance angle and corner radius**.

High strength due to **strengthened core**.

No. of teeth Z: 2

Helix angle: 30 degrees

Shank: DIN 6535 HA to h6

No. of teeth Z: 2

Flute length L_c : 12 mm

Corner radius R_1 : 4 mm

Overhang length L_1 incl. recess: 38 mm

Recess Ø D_1 : 11 mm

Overall length L: 83 mm

Technical description

Shank Ø D_s	12 mm
No. of teeth Z	2
Flute length L_c	12 mm
Corner radius R_1	4 mm
Cutting edge Ø D_c	12 mm
Overall length L	83 mm
Recess Ø D_1	11 mm

Feed f_z for side milling in short-chipping aluminium	0.07 mm
Feed f_z for copy milling in short-chipping aluminium	0.079 mm
Overhang length L_1 incl. recess	38 mm
Shank	DIN 6535 HA to h6
Helix angle	30 degrees
Coating	DLC
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	W
Tolerance nominal \varnothing	e8
Direction of infeed	horizontal, oblique and vertical
Cutting width a_e for milling operation	0.05×D for copy milling
Cutting width a_e for milling operation	0.5×D for side milling
Through-coolant	no
Shank tolerance	h6
Colour ring	yellow
Type of product	End mill

Services

Shank clamping flats for shrink-fit chucks, with retainer function Shank \varnothing tool 12 mm	SZ2025 12
Shank grinding Type HB	129100 HB