

## Garant

**Solid carbide torus cutter, uncoated, Ø h6 DC / R1: 6/1,0 mm**



### Order data

Order number	206190 6/1,0
GTIN	4045197591692
Item class	11X

### Description

#### Version:

**Eccentric relief ground**, additionally **polish ground** in the flutes for **outstanding chip evacuation** in long-chipping aluminium workpieces.

Tolerances:

#### · Corner radius

**$R_1 = 0.5$  tolerance  $\pm 0.02$ .**

**$R_1 > 0.5 - 1.5$  tolerance  $\pm 0.03$ .**

**$R_1 > 1.5$  tolerance  $\pm 0.05$ .**

No. of teeth Z: 3

Helix angle: 45 degrees

Shank: DIN 6535 HA to h6

Balance quality with shank: G 2.5 with HA

No. of teeth Z: 3

Flute length  $L_c$ : 13 mm

Corner radius  $R_1$ : 1 mm

Overhang length  $L_1$  incl. recess: 19 mm

Recess  $\varnothing D_1$ : 5.7 mm

Overall length L: 57 mm

### Technical description

Feed $f_z$ for copy milling in short-chipping aluminium	0.03 mm
Recess $\varnothing D_1$	5.7 mm
Corner radius $R_1$	1 mm
Feed $f_z$ for side milling in short-chipping aluminium	0.03 mm

Cutting edge $\varnothing D_c$	6 mm
No. of teeth Z	3
Overhang length $L_1$ incl. recess	19 mm
Shank $\varnothing D_s$	6 mm
Flute length $L_c$	13 mm
Overall length L	57 mm
Balance quality with shank	G 2.5 with HA
Shank	DIN 6535 HA to h6
Helix angle	45 degrees
Coating	uncoated
Tool material	Solid carbide
Standard	DIN 6527
Type	W
Tolerance nominal $\varnothing$	h6
Direction of infeed	horizontal, oblique and vertical
Cutting width $a_e$ for milling operation	0.05×D for copy milling
Cutting width $a_e$ for milling operation	0.5×D for side milling
Through-coolant	no
Shank tolerance	h6
Colour ring	yellow
Type of product	End mill

## Services

Shank recess Type FRST	209900 FRST
Shank grinding Type HB	129100 HB