

Garant

Solid carbide torus cutter TPC, uncoated, Ø h6 DC / R1: 8/1,0 mm



Order data

Order number	206210 8/1,0
GTIN	4045197811844
Item class	11X

Description

Version:

Eccentric relief ground, additionally **polish ground** in the flutes for **outstanding chip evacuation** in long-chipping aluminium workpieces.

With double chip-breaker for exemplary chip formation.

Application:

Especially for **MTC (Multi Task Cutting)** use on the new generation of turning / milling centres.

Note:

$a_{e\max} = 0.12 \times D$ for TPC machining.

h_{\max} : The values stated in the table are maximum values.

No. of teeth Z: 3

Helix angle: 45 degrees

Shank: DIN 6535 HA to h6

Balance quality with shank: G 2.5 with HA

No. of teeth Z: 3

Flute length L_c : 33 mm

Corner radius R_1 : 1 mm

Overhang length L_1 incl. recess: 40 mm

Recess Ø D_1 : 7.4 mm

Overall length L: 80 mm

Technical description

No. of teeth Z	3
Recess Ø D_1	7.4 mm
Cutting edge Ø D_c	8 mm
Shank Ø D_s	8 mm

Flute length L_c	33 mm
Shank form	HA
Overhang length L_1 incl. recess	40 mm
Corner radius R_1	1 mm
Overall length L	80 mm
Average chip thickness h_{max} for TPC milling in short-chipping aluminium	0.045 mm
Balance quality with shank	G 2.5 with HA
Shank	DIN 6535 HA to h6
Helix angle	45 degrees
Coating	uncoated
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	W
Tolerance nominal \varnothing	h6
Helix angle characteristic	unequal spacing
Direction of infeed	horizontal, oblique and vertical
Cutting width a_e for milling operation	$0.12 \times D$
Through-coolant	no
Machining strategy	TPC
Colour ring	yellow
Type of product	End mill

Services

Shank grinding Type HB	129100 HB
------------------------	-----------